



## uTrust 2700 R

### uTrust Contact Smart Card Reader

- **READY TO USE**  
Driver support for all major PC operating systems
- **SUPPORTS ALL APPLICATIONS**  
Supports all major smart card ICs and technologies in just one device
- **FAST**  
Transaction time optimized for maximum end-user acceptance
- **CONVENIENT**  
Ultra-compact and robust design streamlined for mobile operation
- **SMARTOS™ POWERED**

Identiv's uTrust 2700 R is the ideal PC-linked USB contact smart card reader for a huge variety of secure applications. Providing full compliance with all major industry standards, such as ISO/IEC 7816, USB CCID, PC/SC, and Microsoft WHQL, uTrust 2700 R works seamlessly with virtually all contact smart cards and PC operating systems. Full support and compliance to EMV 2011 and GSA FIPS 201 expands daily use to applications requiring additional security and data protection.

uTrust 2700 R represents the perfect mix between modern stylish design, ergonomic handling, and a compact footprint. The extended card data transmission rate of up to 600 kbps with the support of TA1=97 enables the shortest possible transaction time for maximum end-user convenience.

The Identiv-specific SmartOS™ features easy and complete support of all major contact smart cards. With uTrust 2700 R, the end user experiences convenience, transaction-time efficiency, security, and reliability for applications such as network log-in, Windows authentication and Single Sign-On (SSO), banking and cashless payment applications, as well as high-security use cases for federal governments.

**OPTIONAL ACCESSORY:**

uTrust 2700 R Stand Kit

*Advisory note: Identiv is rebranding the CLOUD products under the uTrust brand name. If you have further questions, please use the contact details provided below.*

PARAMETER	IDENTIV UTRUST 2700 R
Host Interface	USB 2.0 Full Speed (12 Mbps)
<b>Smart Card Interface</b>	
Supported Standards	<ul style="list-style-type: none"> <li>• ISO/IEC 7816 Part 1 to 4</li> <li>• EMV 2011 Ver 4.3 Level 1</li> </ul>
Supported Tag ICs	All major ISO/IEC 7816 compliant smart card IC support
Smart Card Protocols	T=0, T=1
Smart Card Interface Speed	<ul style="list-style-type: none"> <li>• Up to 600 kbps (depending on card)</li> <li>• TA1=97</li> </ul>
Smart Card Clock Frequency	ISO/IEC 7816 compliant; Operates up to 16 MHz
Supported Smart Card Types	5V, 3V and 1.8V, ISO/IEC 7816 Class A/B/C
Power to Smart Card	60mA in Class A; 55mA in Class B; 35mA in Class C

PARAMETER	IDENTIV UTRUST 2700 R	
Smart Card Detection	<ul style="list-style-type: none"> <li>• Card present switch</li> <li>• Automatic power on/off</li> <li>• Short circuit protection</li> </ul>	
Card Size	ID-1	
Contact Type	<ul style="list-style-type: none"> <li>• 8 pin ID-1 sliding contact socket</li> <li>• C4/C8 support</li> <li>• Card detect switch</li> </ul>	
<b>Driver and Software</b>		
PC/SC Driver	PC/SC Specification Ver. 2.01.14 for: <ul style="list-style-type: none"> <li>• Windows® 7/8/10 (32 and 64 bit); Windows® Server 2003/2008/2012</li> <li>• MacOS 10.9.x, 10.10.x, 10.11.x</li> <li>• Linux 2.6.x, 3.x (32 and 64 bit)</li> </ul>	
Software	<ul style="list-style-type: none"> <li>• PC/SC API</li> <li>• CT-API (through wrapper on top of PC/SC)</li> <li>• M-Card API (through wrapper on top of PC/SC)</li> </ul>	
<b>Operating Conditions</b>		
Power Supply	Bus-powered USB	
Power Consumption	<6mA excluding card; 25mA including card	
Dimensions	70 x 60 x 16 mm (2.756 x 2.362 x 0.629 in)	70 x 63 x 62 mm (2.756 x 2.480 x 2.441 in)
Weight	66 g ± 5% (0.15 lb ± 5%)	204 g ± 5% (0.45 lb ± 5%)
Operating Temperature Range	0° to 50°C (32° to 122°F)	
Storage Temperature Range	-20° to 60°C (-4° to 140°F)	
Operating Humidity Range	Up to 95% RH non-condensing	
Durability	Sliding Contact 100,000 card insertions	
MTBF	~7M hours	
Connector	1.5 m USB cable with USB type A connector	
Status Indicator	LED	
Firmware	SmartOS™	
Firmware In-Field Upgradeable	No	
<b>Certifications and Compliances</b>		
Systems/Standards	EMV 2011 Ver 4.3 Level 1, ISO/IEC 7816, USB 2.0 Full Speed, CCID, Microsoft® HCK	
Regulatory /Environmental	CE, FCC, UL 60950, VCCI, GSA APL, RoHS2, REACH, WEEE	
<b>Ordering Information</b>		
Product Part Number	905369-1, 905418 (optional stand kit)	

Identiv, Inc. (NASDAQ: INVE) is the leading global player in physical security and secure identification. Identiv's products, software, systems, and services address the markets for physical and logical access control and a wide range of RFID-enabled applications. Customers in the government, enterprise, consumer, education, healthcare, and transportation sectors rely on Identiv's access and identification solutions. Identiv's mission is to secure the connected physical world: from perimeter to desktop access, and from the world of physical things to the Internet of Everything.

Identiv has offices worldwide. Addresses and phone numbers are listed at [identiv.com/contact](http://identiv.com/contact). For more information, visit [identiv.com](http://identiv.com) or email [sales@identiv.com](mailto:sales@identiv.com).